


CF12.5HA-1



















- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Rear focusing system provides improved performance in macro photography.
- Wide-aperture (F1.4) design achieves
- clear images under low light intensity. Low-distortion design achieving
- accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.

	68.5
28.1	15 9 9 9 9 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

	Focal Length (mm)		12.5	
	Iris Range		F1.4 ~ F22	
	Operation	Focus	Manual	
		Iris	Manual	
	Angle Of View (HXV)	1"	54°13′ × 42°01′	
		2/3"	38°47′ × 29°35′	
		1/2"	28°43′ × 21°44′	
	Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.1	
	Object Dimensions	1"	120 × 90	
	at M.O.D.	2/3"	83 × 62	
	(H × V) (mm)	1/2"	60 × 45	
	Back Focal Distance (in air) (mm)		16.07	
	Exit Pupil Position (From Image Plane) (mm)		-101	
	Filter Thread (mm)		M49 × 0.75	
	Mount		С	
	Mass (g)		290	


Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus



For FA/Machine Vision Fixed Focal

CF16HA-1


















- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Rear focusing system provides improved performance in macro photography.
- Wide-aperture (F1.4) design achieves clear images under low light intensity.
- Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



Focal Length (mm)		16
Iris Range		F1.4 ~ F22
Operation	Focus	Manual
	Iris	Manual
Angle Of View	1"	43°36′ × 33°24′
	2/3"	30°45′ × 23°18′
(11/24)	1/2"	22°37′ × 17°04′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.1
Object Dimensions	1"	100 × 75
at M.O.D.	2/3"	69 × 51
(H×V) (mm)	1/2"	50 × 37
Back Focal Distance (in air) (mm)		17.99
Exit Pupil Position (From Image Plane) (mm)		-172
Filter Thread (mm)		M49 × 0.75
Mount		С
Mass (q)		280

Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus



CF25HA-1








- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Wide-aperture (F1.4) design achieves
- clear images under low light intensity.

 Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.




Facal Landle		OF.
Focal Length (mm)		25
Iris Range		F1.4 ~ F22
Operation	Focus	Manual
	Iris	Manual
Angle Of View	1"	28°43′ × 21°44′
	2/3"	19°58′ × 15°02′
(HAV)	1/2"	14°35′ × 10°58′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.1
Object Dimensions	1"	65 × 48
at M.O.D.	2/3"	44 × 33
(H×V) (mm)	1/2"	32 × 24
Back Focal Distance (in air) (mm)		22.32
Exit Pupil Position (From Image Plane) (mm)		-140
Filter Thread (mm)		M49 × 0.75
Mount		С
Mass (g)		310

Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus

For FA/Machine Vision Fixed Focal


CF35HA-1







- · High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Wide-aperture (F1.4) design achieves clear images under low light intensity.
 Low-distortion design achieving
- accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



Focal Length (mm)		35
Iris Range		F1.4 ~ F22
Onesetien	Focus	Manual
Operation	Iris	Manual
Angle Of View	1"	20°43′ × 15°37′
	2/3"	14°20′ × 10°46′
(HAV)	1/2"	10°27′ × 7°51′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.2
Object Dimensions	1"	73 × 55
at M.O.D. (HXV) (mm)	2/3"	50 × 38
	1/2"	37 × 27
Back Focal Distance (in air) (mm)		14.99
Exit Pupil Position (From Image Plane) (mm)		-37
Filter Thread (mm)		M49 × 0.75
Mount		С
Mass (g)		180

Remarks

- · With Metal Mount
- · With Locking Knob for Iris and Focus



CF50HA-1

FIXED




/ETAL





- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Wide-aperture (F1.8) design achieves clear images under low light intensity, despite the long focal distance.
- Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



MANUAL

Focal Length (mm)		50
Iris Range	1	F1.8 ~ F22
Operation	Focus	Manual
	Iris	Manual
Angle Of View (HXV)	1"	14°35′ × 10°58′
	2/3"	10°03′ × 7°33′
	1/2"	7°19′ × 5°30′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.4 *1
Object Dimensions at M.O.D. (HXV) (mm)	1"	101 × 76
	2/3"	70 × 52
	1/2"	51 × 38
Back Focal Distance (in air) (mm)		17.81
Exit Pupil Position (From Image Plane) (mm)		-49
Filter Thread (mm)		M49 × 0.75
Mount		С
Mass (g)		235

Remarks


- With Metal Mount
- With Locking Knob for Iris and Focus
- *1 Using an extension tube longer than 5mm will increase the M.O.D. to 0.3m.



For FA/Machine Vision Fixed Focal

CF75HA-1

FIXED




C-mt

METAL





- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Wide-aperture (F1.8) design achieves clear images under low light intensity, despite the long focal distance.
- Low-distortion design achieving accurate image input.
- Robust enclosure resistant to vibrations and shocks. Equipped with locking knobs for the iris and the focus.



MANUAL

Focal Length (mm)		75
Iris Range	1	F1.8 ~ F22
Operation	Focus	Manual
Operation	Iris	Manual
Angle Of View	1"	9°45′ × 7°19′
	2/3"	6°43′ × 5°02′
(11/4)	1/2"	4°53′ × 3°40′
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.9 *2
Object Dimensions	1"	147 X 111
at M.O.D.	2/3"	101 X 76
(H×V) (mm)	1/2"	74 × 55
Back Focal Distance (in air) (mm)		24.43
Exit Pupil Position (From Image Plane) (mm)		-52
Filter Thread (mm)		M49 × 0.75
Mount		С
Mass (g)		295

Remarks

- With Metal Mount
- With Locking Knob for Iris and Focus
- *2 Using an extension tube longer than 5mm will increase the M.O.D. to 0.5m.